

Henan Yibo Technology Co., Ltd. — Datasheet

ANIMAL FEED/GRAIN HOSE | HIGH WEAR RESISTANT · ANTI-STATIC · SUCTION / VACUUM RATED

Hose Construction Structure: Inner rubber layer: wear-resistant natural rubber (brown). reinforcement layer: high-strength tire cord plus spiral steel wire, with two additional conductive stainless steel ropes. outer rubber layer: special synthetic rubber, with wear resistance, ozone resistance and weather resistance.; Application: Application: suitable for feed mills, farm feeding lines, grain silos and grain suction equipment. for negative pressure suction and positive pressure conveying of corn, wheat, rice, pellet feed, powdered feed and other grains and livestock feed. used for silo transfer, loading and unloading, automatic feeding in farms. equipped with conductive ropes to eliminate static electricity and prevent dust static hazards.; Temperature Range: -40■-80■

Hose Features -40°C~+80°C: service window; OEM: customization and private label; Third-party: inspection on request; Factory-direct: one plant, cutting through testing

I.D mm	O.D mm	W.P bar	psi	B.P bar	psi	MIN. BENDING RADIUS mm	WEIGHT kg/m	SOFT HEAD LENGTH cm
102	118	4	58	12	174	350	3.88	10

Values are reproduced from the official YIBO product page. psi values are converted at 1 MPa = 145.038 psi and rounded. Working pressure and minimum burst pressure are quoted per code; final confirmation is subject to the factory data sheet at order placement. · +86 137 2136 0724 · sales@dohose.com