

Henan Yibo Technology Co., Ltd. — Datasheet

HIGH PRESSURE STEAM HOSE | STEAM / HOT WATER · HIGH PRESSURE · -30°C~+164°C · 8 sizes

Hose Construction Structure: The inner and outer tube layers of the hose are both made of synthetic rubber with excellent heat resistance.; Application: Suitable for conveying saturated steam and other thermal mechanical equipment.; Temperature Range: -30■ to +164■.

Hose Features -30°C~+164°C: service window; OEM: customization and private label; Third-party: inspection on request; Factory-direct: one plant, cutting through testing

NOMINAL BORE	NOMINAL BORE	NUMBER OF BRAIDED LAYERS	SATURATED STEAM PRESSURE	MINIMUM BEND RADIUS	REFERENCE OUTER DIAMETER	REFERENCE WEIGHT	HOSE LENGTH	HOSE LENGTH
TOLERANCE	TOLERANCE	DIMENSIONS(m)	TOLERANCE(mm)					
±0.8	±0.8	1	0.39	150	25	0.6	±70	±70
±0.8	±0.8	1	0.39	170	28	0.7	±70	±70
±0.8	±0.8	1	0.39	210	31	0.8	±70	±70
±0.8	±0.8	1	0.39	240	34	0.9	±70	±70
±0.8	±0.8	1	0.39	270	37	1	±70	±70
±1.2	±1.2	1	0.39	350	44	1.2	±70	±70
±1.2	±1.2	1	0.39	400	50	1.3	±70	±70

Values are reproduced from the official YIBO product page. Working pressure and minimum burst pressure are quoted per code; final confirmation is subject to the factory data sheet at order placement. · +86 137 2136 0724 · sales@dohose.com