

Henan Yibo Technology Co., Ltd. — Datasheet

ULTRA HIGH-PRESSURE CLEANING HOSE (ULTRA ABRASION RESISTANT) | HIGH WEAR RESISTANT · OIL & FUEL · HIGH PRESSURE

Hose Construction Structure: THE HOSE CONSISTS OF AN INNER TUBE, ONE LAYER OF STEEL WIRE BRAIDING, AND AN OUTER COVER.; Application: SUITABLE FOR CONVEYING PETROLEUM-BASED HYDRAULIC FLUIDS SUCH AS ALCOHOL, HYDRAULIC OIL, LUBRICATING OIL, AND EMULSIONS, ETC. NOT SUITABLE FOR PHOSPHATE ESTER-BASED FLUIDS.; Temperature Range: 0■ TO +70■; FOR WATER MEDIUM: 0■ TO +70■.

Hose Features ISO 9001: quality system with in-house laboratory; 1000 bar / 2500 bar: working and burst pressure published; 5: published sizes quoted by code; OEM: customization and private label

INSIDE DIAMETER ■ID■mm (min)	INSIDE DIAMETER ■ID■mm (max)	OUTSIDE DIAMETER ■OD■mm (min)	OUTSIDE DIAMETER ■OD■mm (max)	MAXIMUM WORKING PRESSURE W.P (Mpa)	psi	MAXIMUM WORKING PRESSU
5.5	6.5	14.7	15.7	22.5	3,263	90
8.5	16.5	17.5	21.5	88	12,763	115
10.5	18.8	19.8	18	72	10,443	125
9.7	10.1	21.3	21.7	100	14,504	250
10.1	24.5	24.9	100	250	36,260	300

Values are reproduced from the official YIBO product page. psi values are converted at 1 MPa = 145.038 psi and rounded. Working pressure and minimum burst pressure are quoted per code; final confirmation is subject to the factory data sheet at order placement. · +86 137 2136 0724 · sales@dohose.com