

Henan Yibo Technology Co., Ltd. — Datasheet

WEAR RESISTANT FULL RUBBER HOSE | HIGH WEAR RESISTANT · CHEMICAL RESISTANT · FOOD GRADE

Hose Construction Structure: Structure: integral extruded molding, no braided or steel wire reinforcement skeleton. the inner and outer layers are made of the same rubber material with homogeneous wall, soft texture and excellent bending performance. ## ■ ■■; Application: Application: used for low-pressure fluid transport and vacuum suction, pipeline support for small equipment. it can transport water, air, weak acid and weak alkali, some light media. widely used in laboratories, light industry, equipment support, sanitation, food transport and other low-pressure working conditions.; Temperature Range: -20■ ~ +80■

Hose Features Factory-direct: one plant, cutting through testing; ISO 9001: quality system with in-house laboratory; 102–600 mm: bore range covered; 11: published sizes quoted by code

ITEM CODE	I.D mm	WALL THICKNESS WT (mm)	MAX LENGTH m
NRF102	102	4 ~ 6	5
NRF127	127	4 ~ 6	5
NRF152	152	4 ~ 6	5
NRF203	203	4 ~ 6	5
NRF254	254	4 ~ 6	5
NRF304	304	4 ~ 6	5
NRF355	355	4 ~ 6	5
NRF406	406	4 ~ 6	5
NRF457	457	4 ~ 6	5
NRF508	508	4 ~ 6	5
NRF600	600	4 ~ 6	5

Values are reproduced from the official YIBO product page. Working pressure and minimum burst pressure are quoted per code; final confirmation is subject to the factory data sheet at order placement. · +86 137 2136 0724 · sales@dohose.com